Southface Energy Institute

responsible solutions for environmental living

- Education and Research
- Policy
- Green Building Services
 - -commercial
 - -residential
 - -communities
- Greenprints
 March 22-23, 2007






www.southface.org


Southface Energy and Environmental Resource Center

- Conserves natural resources
- Reduces air and water pollution
- Provides a healthy indoor environment
- Saves money





The Southeast's first Energy Star building



Eco Office

- Off-the-shelf technology
- Integration is key
- ID and eliminate market barriers









Buildings Have BIG Impact






- Use 30-40% of total US energy
- 60-70% of electricity
- 35-40% of municipal solid waste
- 25-30% of wood & raw materials use
- 25% of water use





Combining the annual energy required to operate residential, commercial, and industrial buildings along with the embodied energy of industry produced building materials like carpet, tile, glass, and concrete exposes buildings as the largest energy consuming and greenhouse gas emitting sector.



"Unknowingly, the architecture and building community is responsible for almost half of all U.S. greenhouse gas emissions annually. Globally the percentage is even greater."

- Guidelines
- Training
- Technical assistance
- 3rd party verification
- Marketing
- Financial incentives

Georgia
South Carolina
Virginia
Tennessee
Alabama





EarthCraft Scope

- Single-family new home and renovation
- Multi-family new home and renovation
- Affordable housing
- Communities
- Adapted by other locales










Westbrook EarthCraft House

- DOE Building America and Zero Energy Homes programs
- EarthCraft House™ and ENERGY STAR® certified





Hedgewood Properties

Carter Woods

Richmond Better Housing Coalition

- 154-unit elderly, Federal Low Income Housing Tax Credit Project
- EarthCraft House features added less than 1.5% to cost
- Green Features include:

 Energy Star Rating
 airtight ducts and envelope
 fibrous cement siding
 blown cellulose insulation
 low-e windows
 low flow water features







The Eco Office Overview

- 10,000 sf offices & training space
- Green Building Showcase
- 75% water use reduction
- Capture 2-year storm
- 60% energy use reduction
- Tracking LEED-Platinum



Image courtesy of Lord, Aeck, and Sargent Architects







Water Technologies



ACF Environmental rain tank

- Efficient fixtures
- Composting system
- Rainwater harvest
- Porous paving
- Green roof
- Rain gardens
- Water-efficient landscaping




Site Demand Reduction – Green Roof Vegetation





Mulched planting beds

Site Demand Reduction - Rain Garden



Images courtesy Ecos Environmental Design



Rain gardens minimize storm water runoff

Eco Office Plumbing Diagram






Public Level - 100 occupants

Commercial Office Water Use

Domestic Water Use





Toilets



- Conventional 1.6 GPF
- 60,000 gallons / year



Toilets





















Dual-Flush Toilet

Lower level toilets

- Caroma USA, Caravelle
- Standard plumbing
- 1.6gpf / 0.8 gpf
- 100 occupants
- Savings 20,000 gal/year





Image courtesy of Caroma USA

Waterless Urinal

Lower level urinals

- Sloan Valve Company, Waterfree
- No supply / flush valve
- 0.0 gpf
- 100 occupants (50%)
- Savings -25,000 gal/year



Image courtesy Sloan Valve Company



Foam-Flush Composting Toilet

Upper level toilets

- Clivus Multrum
- 4" waste line eliminates Black Hole
- Water/biodegradable soap
- 6 oz. per flush (3%)
- 20 occupants
- Savings -20,531 gal/year





Image courtesy of Clivus Multrum



Compost Bin and Tank

- 110 flushes/day peak
- Compost once / year
- Compost tea 4 gallons/day
- Tea once / month





Source: E Source 1997

Low-flow, Automatic Faucet

All lavatories for public & staff

- Conventional faucet 2.5 gpm
- Sloan Valve Company, Solis
- 0.5 gpm, PV recharge
- Savings 47,250 gal/year
- 42% of total demand reduction





Image courtesy of Sloan Valve Company



Annual Water Use Reduction




■ Foam-Flush Savings
■ Dual-Flush Savings
■ Waterless Urinal Savings
■ Low-Flow Lavatory Savings



Summary

- Base Case -201,000 gal/year
- Design Case 88,219 gal/year
- Reduction $-\frac{112,781}{}$ gal/year
- 56% Reduction






Responsible Solutions for Environmental Living

Annual waterfall in Atlanta averages over 50"

Water Use Reduction Results





LEED Water Results – 6 to 7 points

- WE 1 Water Efficient Landscaping
 - No potable water for irrigation
 - 2 points
- WE 2 Innovative Wastewater Technologies
 - 80% reduction (52% without rooftop cistern)
 - 1 point
- WE 3 Water Use Reduction
 - 74% reduction
 - 2 points
- ID 1 Innovation in Design
 - − Exemplary Water Use Reduction (WE 3) − 1 point
 - Possible Exemplary Innovative Wastewater (WE 2) 1 point



Water and Electricity

- Potable water requires vast amounts of energy for purification and delivery; waste treatment requires energy
- Power generation utilizes large quantities of fresh water creating thermal pollution and consumptive loss





Water conservation = Energy conservation Energy conservation = Water conservation

Electricity and Water

3 gallons of water are used to produce each kilowatt-hour


Source: Southern States Energy Board

Base Case Electricity = 144,094 kWh

 \rightarrow 432,282 gallons/year

Eco Office Electricity = 64,804kWh

 \rightarrow 194,412 gallons/year



Georgia Total water use-6,490 million gallons per day (Mgal/d)




Energy Strategy

- Examine Base Building
- Reduce Loads
- Meet Remaining Loads Efficiently
- Green Energy Supply



Heating & Cooling Load Components Base Building



Priorities

- Lighting
- Moisture removal
- Space conditioning



Daylight Modeling



Lumen Micro Simulation



Optimizing South Facade




Image courtesy of Lord, Aeck and Sargent

94% of glazing is located on north and south, maximizing daylight while restricting solar heat gain in warmer months



Nysan Shading Devices



Image courtesy of Nysan Shading Systems, Ltd.

- •External shade blinds
- •Roof-mounted anemometer signals blinds to close in high winds



Sun Control and Daylighting






Image courtesy of Nysan Shading Systems, Ltd.

- •Bottom-up shades in 3rd floor workspace on south elevation
- •Interior light shelves reduce glare and maximize daylighting
- •Sloped ceiling bounces daylight into interior



Epic Metals Roof Deck System

- •Long spans (50ft) reduce framing
- •Acoustic and aesthetic qualities eliminate need for ceiling finishes
- •Can be fabricated from 100% recycled steel
- •Ribbed panels allow for Solatube Skylights without need for framing
- •Light color reflects daylight



EPIC Metals Corporation



Artificial Lighting

- •Integrated automatic controls allowing artificial lighting to dim and brighten to balance daylight
- •Lights organized in separate bays for precision control
- •Efficient florescent lighting technology with anti-glare design
- Excellent color rendering
- Occupancy sensors



Acuity Brands Lighting



Building Envelope

Continuous Air, Thermal and Moisture Barriers

- Polysteel Insulated Concrete Forms (ICF)
- 40% recycled fly ash and slag content of concrete
- ICF is resource efficient and reduces waste
- Cost effective alternative to light gauge steel





Hi-performance Glazing

- Operable, wood frame, aluminum clad windows
- Low-E glazing
- View glazing and daylight glazing on south
- Limited glazing on east and west
- Electro-chromatic glazing on east
- Solatubes








Mechanical Systems- Highlights

- Optimized Heat Pumps
- Dedicated Outside Air System (DOAS)
- Displacement Ventilation
- Fabric Ducts
- Integrated System









Optimized Heat Pumps

- •High efficiency, dual speed Carrier air-to-air heat pumps (SEER 16)
- •Harvested rainwater sprayed on EcoMesh cage enhances efficiency through evaporative cooling
- •Five separate zones and central mechanical room for efficient air distribution
- •All ductwork in conditioned space




Image courtesy of *EcoMESH*TM




Dedicated Outside Air System (DOAS)

Provides 100% fresh air for occupants


Decouples latent and sensible loads utilizing 3 separate energy efficient technologies:

- dew point indirect evaporative cooler (Coolerado)
- enthalpy recovery wheel (Greenheck)
- liquid desiccant dehumidification system (Drycor)

Image courtesy Coolerado Cooler










Displacement Ventilation

- •Raised floor allows for flexible workspace and easy re-wiring
- •Minimizes volume of conditioned space by utilizing the stack effect, conditioning only lower air space
- •Underfloor air distribution offers economic, architectural and health benefits







Integrated Controls

- Johnson Control's Knowledge
 Based Integration provides single
 point of responsibility for design,
 delivery, warranty, and
 commissioning
- Integrated HVAC, fire detection, and security systems
- PEMs allow individual control of temperature, air flow, task lighting, and white noise






Image courtesy of Johnson Controls

Herman Miller Resolve System


- •Honeycomb shaped system for open work stations
- •Each module maximizes 120 radial degrees of work space
- •Modular units allow for flexible office





Sustainable Materials - Fabric Duct

- Washable; improves air quality
- Permeable material reduces noise and prevents condensation
- Easier to fabricate and install than conventional metal ducts
- Engineered nozzles for precise control of airflow





KONE EcoSpace Elevator




Compared to hydraulic elevators:

- •Uses 60% less energy
- •Generates 60% less heat
- •Creates 30% less noise
- •Uses no oil
- •Requires minimal floor area


(\sim 5 s.f.) for controls




Successful Energy Efficiency Measures











We would need to produce 5.5 times the energy produced by the PV canopy to fill all our energy needs. The PV arrays would need to extend across our site.



Renewable Choice

- •Southface is powered by 100% clean, renewable American Wind
- •Our purchase of 80.000 kWh prevents 111,360 pounds of CO2 pollution
- •That's the equivalent of planting 15 acres of trees






Lucid Design Group

- •Real time monitoring and display of environmental performance
- •Window to living building











www.davis-langdon.us

IKEA Stoughton, MA

- 350,277 square feet conditioned space
- LEED™ Certified (in process)
- The majority of parking is underneath the building, both to reduce building footprint and minimize heat gain
- 22,000 sq. ft. green roof captures and filters up to 75 percent of rooftop runoff
- Rainwater collection system holds up to 60,000 gallons of rainwater to meet irrigation needs





- Installed waterless urinals
- Provided showering facilities for those who bike to work
- Diverted nearly 85% of their construction waste from landfills
- Used building materials with a collective recycled content of 33%
- Utilized 86% certified wood




Using energy modelling software (VisualDOE), IKEA Stoughton was found to perform at a 38% improvement over energy code.

Energy Efficiency Measures include:

- A significantly lower lighting power density in the retail and showroom areas
- Additional Insulation in the roof and wall assemblies
- A low ratio of glazing combined with high-performance glass
- High efficiency split system package units





The 38% energy efficiency improvement resulted in a savings of \$167,000 per year.



LEED™ Scorecard

Project D9242083ELIQELF - IKEA Stoughton

_	0		Project Score d 36 to 32 points - Silver 30 to 38 points - Gold 39 to 51 points - Plasinum 52	or more	poin	1		Possible Points	-00
3	0		inable Sites Possible Points 14	7	0	0	Mater	ials & Resources Possible Points	100 1
	†	N	39-38-38-38-38-38-38-38-38-38-38-38-38-38-	Y		11	45-70	CHARLES LOCKYANO MORNO VICENTIC	
4	- 1	Prorest.	Erosion & Sedimentation Control 0	Y			Products §	Storage & Collection of Recyclables	-
		1 Credit 1	Site Selection 1	-		1	1.1 Huer	Building Rouse, Maintain 78% of Existing Shell	
П		1 0482	Urban Redevelopment 1			1	Delta and	Building Rouse, Maintain 100% of Existing Shell	
- 1		1 Dult 2	Brownfield Redevelopment 1			1	SHIP OF	Building Rouse, Maintain 100%, Shell & 50% Non-Shell	
		1 Cruit 4.1	Alternative Transportation, Public Transportation Access 1	1			Depth 2.1	Construction Waste Management, Diversions	
1		Skilled	Alternative Transportation, Big/ole Storage & Changing Rooms 1	1			Des (# 2.2)	Construction Waste Management, Divert 75%	
	_	1 Dut 43	Alternative Transportation, Alternative Fuel Returing Stations 1	1		1	DWG S.A.	Resource Reuse, Specify 5%	
-		1 Credit 4.4	Alternative Transportation, Paking Capacity 1			1	Dw8 22	Resource Reuse, Specify 10%	
1		1 De811	Reduced Site Diszurbance, Protect or Flestore Open Space 1	1			Swiff 4.1	Recycled Content, Specify 5% (post-consumer + 1/2 post-industrial)	
31	=	1 0+812	Reduced Site Disturbance, Development Foogelet 1	1			Dett 42	Recycled Content, Specify 10% (post-consumer + 1/2 post-industrial)	
		1 Don't 6.1	Stormwater Management, Rate and Quantity 1	1			Dec (8.5.5)	Local Regional Materials, 20% Manufactured Locally	
-	=	1 Ce042	Stormwater Management, Treatment	1			11800	Local Regional Materials, of 20% Above, 50% Hervested Locally	
1	-	Craft 7.1	Landscape & Exterior Design to Reduce Heat Islands, Non-Roof			1	Daniel G	Rapidly Renewable Materials	
1		Oreit72	Landscape & Exterior Design to Reduce Heat Islands. Roof 1	1		-	Deck 7	Certified Wood	
	=	1 Cods	Light Pollution Reduction	-					
_	_			5	0	10	Indoo	r Environmental Quality Possible Points	8
1	0	1 Water	Efficiency Possible Points 5	Y	1	*			
۲	7	iv .	AND THE RESERVE OF THE PROPERTY OF THE PROPERT	Y			Training T	Minimum IAQ Performance	
1	-1	Credit 1.1	Water Efficient Landscaping, Return by tots. 1	Y		4	Francy 2	Environmental Tobacco Smoke (ETS) Control	
1		Owit 12	Water Efficient Landscaping, No Potable Use or No Intgation 1	1			Depoted	Carbon Dioxide (CO ₂) Monitoring	
		1 0+63	Innovative Wassewater Technologies 1	1		1	Dark C	Increase Ventilation Effectiveness	
1	_	Child 2.1	Water Use Reduction, 20% Reduction 1			1	Dw/83.1	Construction IAO Management Plan, During Construction	
1	_	Over 12	Water Use Reduction, 30% Reduction 1			1	Owin 3.2	Construction IAQ Management Plan, Before Occupancy	
				1			Decil 4.5	Low-Emitting Materials, Adventue & Sestents	
8	0	o Estatua	y & Atmosphere Possible Points 17	1			24040	Low-Emitting Materials, Paints	
	7	N	I Sales I Sales I	1		-	Defi 4.3	Low-Emitting Materials, Carpet	
Y	Y	Paris 1	Fundamental Building Systems Commissioning o	1		-	34840	Low-Emitting Materials, Composite Wood	
_	Y	Parel	Minimum Energy Performance o	1		_	Defect.	Indoor Chemical & Pollutant Source Control	
	Ý	Page 1	CFC Reduction in HVAC&R Equipment 0	100		-	Special City	Controllability of Systems, Perimeter	
2	-	Owk 1.1	Optimize Energy Performance, 15% & 20% New Construction 2		-		Dark C.	Controllability of Systems, Non-Permeter	
2	-	Credit 12	Optimize Energy Performance, 25% & 30% New Construction 2			_	Duck T.A.		
2	-	Over 13	Optimize Energy Performance, 35% & 40% New Construction 2			and the same	bud7.2		
-	-	2 Deltis	Optimize Energy Performance, 45% & Son, New Construction 2			and the last	Dealer S. S.	Daylight & Views, Daylight 75% of Speces	
-	-	2 00015	Optimize Energy Performance, 55% a 50% New Construction 2			-	-mer	F. 2. (1. 2. 7. 1. 1. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.	
-	-	others and the same of	Renewable Energy, es.			200		Daying it a views, views so so co openies	
-	-	1 OneEli		-	La	-	PROPERTY	ation & Design Process Possible Points	-
+		1 CHRIS		Bassey	0		mmov	ation a Design Process Possible Points	
		1 Delitzii	Ronowable Energy, con. 1			*			
		1 Over 1	Additional Commissioning	1		_	P. Fabori	Control of the Contro	
1		Dredt 4	Ozone Depletion 1	1	-	_	Death 1.E		
		1 Creft 1	Measurement & Verification 1	1			DMR13	Innovation in Design: Exemplary Local Regional Materials, 40% Menufactured Local	
1		Oracle 6	Green Power 1	1	1		Dedil	LEED™ Accredited Professional	

A study prepared by the **Heschong Mahone Group** in 1999 looked at the influence of daylight in a retail environment.

- Compared sales performance in 108 stores.
- Two thirds had skylights, one third did not.
- Monthly gross sales per store were averaged over an 18-month period.
- Results demonstrated:

Daylighting boosted sales by an average of **40%**.

(http://www.pge.com/pec/daylight/daylight.shtml)



BB's 60,000 sq. foot Amish Grocery in Quarryville, PA uses no electric lighting.

